wherein the communication controller communicates the display unit information to the video source and the display unit receives a signal from the video source that is generated based on at least a portion of the display unit information.

5
~~27~~. (amended) A display unit comprising:

a video circuit adapted to display video signals sent by a video source;

a memory in which at least display unit information is stored, wherein the display unit information includes identifying information of the display unit; and

a communication controller capable of bi-directionally communicating with the video source;

wherein the communication controller communicates the display unit information from the display unit to the video source and the display unit receives a signal from the video source that is generated based on at least a portion of the display unit information.

9
~~32~~. (amended) A method of communicating between a display unit and a video source from which video signals are sent to the display unit for display, the method comprising the steps of:

communicating display unit information stored in a memory of the display unit from the display unit to the video source, wherein the display unit information includes identifying information of the display unit; and

B3

sending a signal from the video source to the display unit, wherein the signal is generated based on at least a portion of the display unit information;

wherein information is bi-directionally communicated with the video source and the display unit.

Please add the following new claims:

--~~34~~ 4. A display unit according to claim ~~26~~ 3, wherein the display unit information includes information that identifies a function of the display unit.

~~35~~ 8. A display unit according to claim ~~29~~ 7, wherein the display unit information includes information that identifies a function of the display unit.

B4

~~36~~ 10. A display unit comprising:

a video circuit adapted to display video signals sent by an externally connected video source;

a memory in which at least display unit information is stored, wherein the display unit information includes identifying information of the display unit; and

a communication controller capable of bi-directionally communicating with the video source;

wherein the communication controller communicates the display unit information from the display unit to the video source and the display unit receives a signal from the video

source that is generated based on the display unit information.

11 10
~~37~~. A display unit according to claim ~~36~~, wherein the video source is a computer.

12 10
~~38~~. A display unit according to claim ~~36~~, wherein the identifying information includes an identification number for identifying the display unit.

B4

13 12
~~39~~. A display unit according to claim ~~38~~, wherein the display unit information includes information that identifies a function of the display unit.

14
~~40~~. A display unit comprising:

means for receiving video signals for display from an externally connected video source;

memory means for storing at least display unit information, wherein the display unit information includes identifying information of the display unit; and

a communication controller capable of bi-directionally communicating with the video source;

wherein the communication controller communicates the display unit information to the video source and the display unit receives a signal from the video source that is generated based on at least a portion of the display unit information.

15 ~~11~~. A display unit according to claim 14 ~~10~~, wherein the video source is a computer.

16 ~~12~~. A display unit according to claim 14 ~~10~~, wherein the identifying information includes an identification number for identifying the display unit.

17 ~~13~~. A display unit according to claim 16 ~~12~~, wherein the display unit information includes information that identifies a function of the display unit.

18 ~~14~~. A display unit comprising:

means for receiving video signals for display from a video signal source externally connected to the display unit;

memory means for storing at least display unit information, wherein the display unit information includes identifying information of the display unit; and

a communication controller capable of bi-directionally communicating with the video signal source;

wherein the communication controller communicates the display unit information to the video signal source and the display unit receives a signal from the video signal source that is generated based on at least a portion of the display unit information.

19 ~~15~~. A display unit according to claim 18 ~~14~~, wherein the video signal source is a computer.

20 ~~46~~. A display unit according to claim 18 ~~44~~, wherein the identifying information includes an identification number for identifying the display unit.

21 ~~47~~. A display unit according to claim 20 ~~46~~, wherein the display unit information includes information that identifies a function of the display unit.

22 ~~48~~. A display unit comprising:

a video circuit adapted to display video signals sent by a video signal source externally connected to the display unit;

a memory in which at least display unit information is stored, wherein the display unit information includes identifying information of the display unit; and

a communication controller capable of bi-directionally communicating with the video signal source;

wherein the communication controller communicates the display unit information from the display unit to the video signal source and the display unit receives a signal from the video signal source that is generated based on at least a portion of the display unit information.

23 ~~49~~. A display unit according to claim 22 ~~48~~, wherein the video signal source is a computer.

24 ~~50~~. A display unit according to claim 22 ~~48~~, wherein the identifying information includes an identification number for identifying the display unit.

25 ~~51~~. A display unit according to claim 24 ~~50~~, wherein the display unit information includes information that identifies a function of the display unit.

26 ~~52~~. A display unit comprising:

a video circuit adapted to display video signals generated based on video information sent by a video information source;

a memory in which at least display unit information is stored, wherein the display unit information includes identifying information of the display unit; and

a communication controller capable of bi-directionally communicating with the video information source;

wherein the communication controller communicates the display unit information from the display unit to the video information source and the display unit receives a signal from the video information source that is generated based on at least a portion of the display unit information.

27 ~~53~~. A display unit according to claim 26 ~~52~~, wherein the video information source is a computer.

28 ~~54~~. A display unit according to claim 26 ~~52~~, wherein the identifying information includes an identification number for identifying the display unit.

29 ~~55~~. A display unit according to claim 28 ~~54~~, wherein the display unit information includes information that identifies a function of the display unit.

30 ~~56~~. A display unit comprising:

a video circuit adapted to display video signals generated based on video information sent by a video information source externally connected to the display unit;

a memory in which at least display unit information is stored, wherein the display unit information includes identifying information of the display unit; and

a communication controller capable of bi-directionally communicating with the video information source;

wherein the communication controller communicates the display unit information from the display unit to the video information source and the display unit receives a signal from the video information source that is generated based on at least a portion of the display unit information.

31 ~~57~~. A display unit according to claim 30 ~~56~~, wherein the video information source is a computer.